# **PCT**

# WORLD INTELLECTUAL PROPERTY ORGANIZATION International Burean



## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6:		(11) International Publication Number:	WO 95/07016
A01B 79/00, A01C 1/00, A01G 7/00	A1	(43) International Publication Date:	16 March 1995 (16.03.95)
(21) International Application Number: PCT/US94/10022 (22) International Filing Date: 8 September 1994 (08.09.94)		DK, ES, FR, GB, GR, IE, IT,	
(30) Priority Data: 08/118,380 8 September 1993 (08.09.93)	) U	Published With international search reports	1.
(71) Applicant: THE PENN STATE RESEARCH FOUNI [US/US]; 207 Old Main Building, University P 16802 (US).			
(72) Inventor: HAMILTON, George, W., Jr.; 2467 Oak Le State College, PA 16803 (US).	af Cou	п.	
(74) Agent: MONAHAN, Thomas, J.; Intellectual Property The Pennsylvania State University, 113 Technology University Park, PA 16802 (US).			•
·		·	

#### (54) Title: PELLETIZED MULCH COMPOSITION AND PROCESS FOR PREPARING SAME

#### (57) Abstract

Process for producing novel mulching pellets from waste paper scrap by incorporating particulate water-insoluble, swellable, gelforming polymer into the pellet-forming composition. The formed pellets swell and disintegrate after being spread and impregnated with water, to increase their area of ground-coverage, to release any included nutrients or seeds, and to deposit polymer particles having water-absorbing properties.

# PELLETIZED MULCH COMPOSITION AND PROCESS FOR PREPARING SAME

#### BACKGROUND OF THE INVENTION

5

10

15

20

25

30

#### 1. Field of the Invention:

Mulching is the practice of applying foreign materials to a seedbed to reduce erosion and provide a more favorable microenvironment for seed germination and seedling development. On level planting beds where the capability for frequent irrigation exists, mulching may not be necessary during propagation. However, mulching can enhance germination and it is almost essential on sloping sites or where moisture availability largely depends on natural rainfall.

An effective mulch serves several functions: it stabilizes the soil and seed against water and wind erosion; it moderates temperature fluctuations at the soil surface and thus protects germinating seeds and seedlings from temperature-induced injury; it reduces evaporation of moisture from the soil surface and provides a more humid microenvironment in and directly above the soil surface, and it dissipates the energy of falling water droplets from rainfall and irrigation to reduce crust formations at the soil surface and thus water infiltration rates are not decreased. Not all mulches serve all of these functions; some are more effective than others, and selection of a particular material depends on the specific requirements at each site and the cost and local availability of materials.

#### 2. Discussion of the Prior Art:

For decades, one of the most widely used mulches has been straw, primarily from wheat plantings. Applied at a rate of 1.5-2.0 tons per acre, it provides acceptable results. Weed-free straw should be used, and as long as coverage is

2

not too heavy (not more than 50 percent soil coverage), the straw need not be removed after seedling emergence.

Grassy hay is similar to straw in its effectiveness as a mulch. Early-season cuttings of hay are preferred, as they are less likely to contain substantial populations of weed seeds.

Straw and hay can be applied by hand to small sites. windy areas, they should be stabilized by crisscrossing the 10 area with binder twine anchored down with stakes. Application to large sites is usually accomplished by using a mechanical mulch blower. This machine chops the material An asphalt binder is and blows it over the seedbed. usually sprayed on the mulch as it exits the blower, or 15 after application, to stabilize the mulch on the seedbed. The same technique can be used for loose wood mulches and organic residues. Typically straw contaminates the seedbed with weed seeds and depletes the seedbed of nitrogen, due to the high C:N ratio of straw. 20

Hydro-mulch is another mulch commonly used for turfgrass establishment. Hydro-mulch can be made from virgin wood fibers, waste paper fiber from various industries, or newsprint. Although hydro-mulch can be stored and is weed free, it requires the use of a hydro-mulcher, which is an expensive piece of equipment, for application. Hydro-mulching also requires the availability of a very large water source, near the application site, to service the hydro-mulching process.

25

30

Reference is made to U.S. Patent 3,269,824 which discloses a process for repulping waste paper of various types into a slurry, adding thereto fertilizer minerals including nitrogen, potassium, phosphorous, etc., drying under vacuum and stamping into dense pellets useful for application as a mulch. Repulping a waste paper requires large amounts of water and expensive equipment, and produces large volumes

3

of contaminated waste water. Also the densified pellets require large amounts of absorbed moisture before expanding to increase ground coverage and to release nutrients.

Reference is also made to U.S. Patent 4,339,890 which discloses a dry seeding hydro-mulch containing shredded or ground particles of waste paper and dry wetting agent, which is sprayed onto the soil after mixing it with water in a hydro-mulcher. Such equipment is expensive and requires access to substantial amounts of water.

Reference is also made to U.S. Patent 4,369,597 which relates to the formulation of pelletized mint mulch suitable for application as a hydro-mulch or in dry form, and which discusses the disadvantages of the waste paper mulch pellets of U.S. Patent 3,269,824, discussed supra.

Finally, reference is made to U.S. Patents 4,123,489; 4,625,679; 4,813,996 and 5,195,465 for their disclosure of processes for pelletizing waste paper particles containing soil nutrients and other ingredients for various uses including soil additives and mulches.

#### SUMMARY OF THE INVENTION

25

30

35

15

20

The present invention provides a novel, economical and ecological process for producing inexpensive and efficient dry mulching pellets containing particulate waste paper and a swelling agent, capable of application by means of simple spreading devices and being highly water-absorbent and water-retentive. Upon impregnation with applied water or rain, the present pellets swell, expand and disintegrate to increase their area of ground coverage and provide a water-absorbing surface covering which prevents water run-off and which helps maintain moisture in the soil. The disintegration or coming-apart of the swollen pellets also increases the exposed surface area of the mulch and facilitates the release of seed and the release of

20

25

30

35

4

nutrients, if present in the pellets, into the soil to support the germination and growth of seed and plants in the soil.

The most essential feature of the process and mulch pellets of the present invention is the incorporation of a swelling agent comprising a water-insoluble, swellable, gel-forming, hydrophilic polymeric material, capable of absorbing substantial amounts of water, into pellets comprising waste paper particles.

# DETAILED DESCRIPTION

The present invention aids the environment by recycling paper products back into the soil, rather than depositing them in landfills or incinerating them. This is made possible by the discovery of a process for producing mulch pellets which consist nearly entirely of particulate waste paper and which contain a minor amount by weight, up to about 10%, most preferably between about 2% and 5%, of a water-soluble, film-forming, polymeric binder material, and a minor amount be weight, up to about 10%, most preferably between about 2% and 5%, of a swelling agent comprising a water-insoluble, water-swellable, gel-forming, hydrophilic polymeric material in particulate form, distributed throughout the pellets.

A principal advantage of the present invention is the ability to use, and recycle, substantial volumes of inexpensive waste paper to produce an advantageous mulch product which can be applied to the soil by a simple and cost-effective spreading process. While waste paper has been shredded and pelletized, per se, such pellets do not provide a suitable mulch because they remain on the soil surface as dense discrete pellets which do not swell and burst or disintegrate to form a good ground cover even after being soaked with water. If applied in sufficient density to cover the surface of the soil against wind or

runoff, they smother the soil and prevent desired growth. If applied in reduced density to permit the desired growth they are ineffective in reducing soil erosion and weed growth.

The present invention overcomes these problems by the discovery that the addition of a small amount of a water-insoluble, water-absorbing, gel-forming polymer into the pellet-forming particulate paper composition transforms the dense pellets into pellets which absorb substantial amounts of water, independently of the water-absorbing properties of the paper itself. This causes the moist pellets to swell and expand apart or burst and disintegrate to reduce their density and substantially-increase their ground-coverage and their mulching ability while, at the same time, donating a valuable hydrated soil additive which remains effective for the storage and release of water near the surface of the soil to assist in seed germination and plant growth.

The present mulch pellets comprise up to about 99% by weight of particulate waste paper, preferably newsprint, which contains a small amount by weight of a water-soluble film-forming binder material such as polyvinyl alcohol and/or a cellulosic binder material such as carboxymethyl cellulose to bind the wood fibers in the paper-making process. Thus the addition of more water-soluble binder materials generally is not necessary.

The essential additive to the present particulate paper pellet-forming compositions is the water-insoluble, water-swellable, gel-forming hydrophilic polymer which is uniformly mixed in powder form, in a horizontal mixer, with the particulate paper, a small amount of water if needed, and optionally, other nutrients, seeds, dyes and/or other optional additives. The composition is fed to a conventional pellet mill, pelletized, and air-dried to a water-content below about 10% by weight.

6

Gel-forming hydrophilic polymer particles are well-known soil additives to impart water-holding and water-releasing properties to soil, turf and potting mixtures. made to cross-linked polyacrylamide commercially-available from Broodleaf Industries, Inc., San Diego, CA under the registered trademark "P4", which are superabsorbent particles having a gel capacity of about 200, i.e., capable of absorbing water up to about 200 times their own weight. Similar cross-linked polyacrylate polymers are used in particulate form as gel-forming, aqueous liquid-retaining materials in diapers and related products.

5

10

15

20

25

30

Reference is made to U.S. Patent 3,973,355 which discloses the incorporation of up to about 5% by weight of a variety of particulate water-insoluble, water-swellable, crosslined polymers in a plant growth foam, which polymers are suitable for use in powder form as swelling agent additives to the present waste paper pellets. In general gel-forming polymers having a gel capacity of at least about 20 and up to about 700 are suitable.

The preferred waste paper for use according to the present invention is ordinary newsprint, which is a non-phytotoxic waste product which is widely-available in most parts of the world. Other non-phytoxic waste paper products such as magazines and paperboard are also useful but may require additional processing to reduce excessive amounts of undesirable fillers such as clay and other ingredients which may be harmful to soil, seeds or plants.

The present pellet-forming compositions are formed from raw waste paper, preferably newsprint, which is hammermilled to

reduce it to fine particulate size, i.e., less than about 1/4 inch in any direction, and stored in a fluff bin. For pelletization, the particulate waste paper is misted with water, if needed, which may include a conventional wetting

7

agent and a water soluble binder material, to provide a water content of about 15% by weight, necessary to enable the particulate paper composition to bind and hold together in pellet form. A portion of the included water is exuded and lost during pelletization, and another portion of the water is removed during final air-drying of the pellets, prior to bagging. The final water-content of the bagged pellets should be below about 10% by weight of water, bound by the swelling agent. Larger amounts of included water can cause the pellets to develop mold in the bags and/or to come apart or swell prematurely.

The second of the second of

10

15

20

25

30

35

The hammermilling or cutting of waste paper into small pieces suitable for pelletization, and processes and pellet mills for the pelletization of such paper pieces are well known in the art. Reference is again made to U.S. Patents 4,123,489; 4,625,679; 4,813,996 and 5,195,465 for their disclosures of processes and machines for shredding, cutting and/or hammermilling of waste papers, including newsprint, and for the processing and pelletizing thereof for a variety of uses. In effect, the present invention involves the uniform incorporation of small amounts of powdered water-absorbing, gel-forming polymers into such pellet-forming compositions to produce pellets which provide excellent mulching properties in that they can be spread or broadcast over the soil as discrete pellets which when wetted, disintegrate swell and open or substantially increase their extent of ground coverage and provide a mulch having the ability to absorb and to release water over a long period of time.

Greenhouse studies were conducted to evaluate the present pellet performance. Flats were filled with soil and then seeded with Kentucky bluegrass. Different batches of identical pellets were applied to different flats at 44, 88 and 176 lb/1000 ft, for comparison with other identical flats to which no mulch pellets were applied. The flats were placed under a rainfall simulator and irrigated with

1", 2.5", or 5" of water. Significant flooding did occur in many flats at the higher irrigation rates and seed floating was observed on many flats. The flats were placed in a greenhouse and irrigated at different intervals, selected to permit drying of the soil surface.

Plant densities were determined in the various flats by counting individual grass plants per unit area. Plant densities are important when considering overall turf quality. Increased plant densities provide increased soil surface protection and soil stabilization, both of which help prevent erosion. Plant density is also important to create good competition to prevent infestations of pests and allow for the turf stand to recover from different types of stress.

Individual tillers (grass plants) were counted in a 36 sq. in. area of each flat. Data are averages of three replications and were as follows:

5

10

15

40

Mulch Rate (lb/M sq ft)	Initial Watering (inch)	Watering Interval (days)	#Tillers
	· · · · · · · · · · · · · · · · · · ·	(	
0	2.5	2	162
44	2.5	2 2 2 2	140
88	2.5	2	261
176	2.5	2	267
		-	
0	5	2	86
44	5	2	172
88	5	2 2 2	233
	•	_	
0	1	4	45
44	ī	4	117
88	1 1 1	4	157
	<del>-</del>	•	
0	2.5	4	45
44 .	2.5	4	73
88	2.5	4	130
176	2.5	4	102
0	•	0	29
44	1	8 8	220
88	1 1 1	8	275
00	1	•	273
0	2.5	8	67
44	2.5	8	88
88	2.5	8	106
176	2.5	8	247

This data indicates that the rate of mulch had a direct effect on the seedling germination and survival. As the rate of mulch increased, the number of tillers increased. Second, the mulch had a much more apparent effect on the seedling survival as the days in between waterings increased. This is expected since one of the purposes of mulch is to prevent the soil surface from drying out and to retain moisture.

It will be apparent to those skilled in the art that the present pellets can be produced in various sizes and densities provided that they can be spread conveniently and will swell and disintegrate immediately upon being impregnated with water. Newsprint generally has a density of 4 to 7 lbs. cu. ft. and, when pelletized according to the present invention, produces pellets having a density of

35-45 lbs/cu. ft., depending upon pellet size. Preferably the present pellets are cylindrical and have a diameter of between about 1/8 and 1/4 inch and a length of between about 1/8 and 1/2 inch. Various wetting agents, dyes, aqueous or dry fertilizers, seeds and other components can be included in the present pellets, as will be apparent to those skilled in the art.

It should be understood that the foregoing description is only illustrative of the invention. Various alternatives and modifications can be devised by those skilled in the art without departing from the invention. Accordingly, the present invention is intended to embrace all such alternatives, modifications and variances which fall within the scope of the appended claims.

#### **CLAIMS**

- 1. Process for producing mulching pellets from waste paper, comprising the steps of reducing said waste paper to finely-divided particle form, uniformly dispersing therein a small amount of a particulate water-insoluble, water-absorbing, swellable, gel-forming polymer to form a pellet-forming composition containing a minor amount by weight of water, pelletizing said composition, and drying to form discrete pellets which contain less than about 10% by weight of water and which swell and rupture when impregnated with water.
- 2. Process according to claim 1 in which said waste paper includes a minor amount by weight of a water-soluble film-forming binder material.
- 3. Process according to claim 1 in which said waste paper comprises newsprint.
- 4. Process according to claim 1 in which said gelforming polymer comprises a cross-linked acrylic polymer in powdered form.
- 5. Process according to claim 1 in which said gelforming polymer is present in an amount up to about 10% by weight of the pellet-forming composition.
- 6. Process according to claim 5 in which the amount of the gel-forming polymer is between about 2% and 5% by weight of the pellet-forming composition.
- 7. Process according to claim 1 in which the formed pellets are cylindrical and have a diameter between about 1/8 inch and 1/4 inch, and have a length between about 1/8 and 1/2 inch.
  - 8. Mulching pellets capable of swelling and

rupturing when impregnated with water, said pellets comprising over 90% by weight of finely-divided waste paper having uniformly dispersed therein an amount, up to about 10% by weight, of a particulate, water-insoluble, water-absorbing, swellable gel-forming polymer.

- 9. Mulching pellets according to claim 8 in which said waste paper includes a minor amount by weight of a water-soluble film-forming binder material.
- 10. Mulching pellets according to claim 8 in which said waste paper comprises newsprint.
- 11. Mulching pellets according to claim 8 in which said gel-forming polymer comprises a cross-linked acrylic polymer in powdered form.
- 12. Mulching pellets according to claim 8 in which said gel-forming polymer is present in an amount between about 2% and 5% by weight of the total composition.
- 13. Mulching pellets according to claim 8 comprising cylindrical pellets having a diameter between about 1/8 inch and 1/4 inch and having a length between about 1/8 inch and 1/2 inch.

## INTERNATIONAL SEARCH REPORT

International application No. PCT/US94/10022

	A. CLASSIFICATION OF SUBJECT MATTER  IPC(6) :A01B 79/00; A01C 1/00; A01G 7/00						
US CL: 47/9, 58 According to International Patent Classification (IPC) or to both national classification and IPC							
	LDS SEARCHED						
	locumentation scarched (classification system follows	ed by classification symbols)					
U.S. : 47/9, 58							
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched							
Electronic o	data base consulted during the international search (n	ame of data base and, where practicable	, search terms used)				
APS, DIALOG							
C. DOC	CUMENTS CONSIDERED TO BE RELEVANT	·					
Category*	Citation of document, with indication, where a	ppropriate, of the relevant passages	Relevant to claim No.				
Y	US, A, 3,812,615 (JAMISON ET AL) 28 MAY 1974, see 1-13 columns 2-3 and 5.						
<b>Y</b>	US, A 5,082,563 (WEBB ET AL) 21 JANUARY 1992, see 1-13 columns 3-5.						
		·					
	•						
Further documents are listed in the continuation of Box C. See patent family annex.							
•	ecial categories of cited documents: current defining the general state of the art which is not considered	"I" later document published after the inte- date and not in conflict with the applica principle or theory underlying the inve	tion but cited to understand the				
to i	be of particular relevance tier document published on or after the international filing date	eXe document of particular relevance; the	claimed invention cannot be				
cite	cument which may throw doubts on priority claim(s) or which is ad to establish the publication date of another citation or other scial reason (as specified)	when the document is taken alone  "Y" document of particular relevance; the	claimed invention cannot be				
*O' do:	comment referring to an oral disclosure, use, exhibition or other	considered to involve an inventive combined with one or more other such being obvious to a person skilled in the	documents, such combination				
	comment published prior to the international filing date but later than a priority date claimed	*&* document member of the same patent i					
	actual completion of the international search BER 1994	Date of mailing of the international search 13DEC 199	rch report				
Name and mailing address of the ISA/US Commissioner of Patents and Trademarks		Authorized officer Q. N	igza ja				
Box PCT Weshington, D.C. 20231							
	# # # # # # # # # # # # # # # # # # #	Talanhara No. (703) 308-0196					